

Package: HMDHFDplus (via r-universe)

October 4, 2026

Type Package

Title Read Human Mortality Database and Human Fertility Database Data from the Web

Version 2.0.14

Date 2026-05-07

Description Utilities for reading data from the Human Mortality Database (<<https://www.mortality.org>>), Human Fertility Database (<<https://www.humanfertility.org>>), and similar databases from the web or locally into an R session as data.frame objects. These are the two most widely used sources of demographic data to study basic demographic change, trends, and develop new demographic methods. Other supported databases at this time include the Human Fertility Collection (<<https://www.fertilitydata.org>>), The Japanese Mortality Database (<<https://www.ipss.go.jp/p-toukei/JMD/index-en.html>>), and the Canadian Human Mortality Database (<<http://www.bdlc.umontreal.ca/chmd/>>). Arguments and data are standardized.

URL <https://github.com/timriffe/HMDHFDplus>

BugReports <https://github.com/timriffe/HMDHFDplus/issues>

License GPL-2

LazyLoad yes

Encoding UTF-8

Depends R (>= 4.1),

Collate 'age2int.R' 'HFDutils.R' 'HMDutils.R' 'readHFD.R' 'readHMD.R' 'userInput.R'

Imports httr (>= 1.4.7), rvest (>= 1.0.5), dplyr (>= 1.1.4), janitor, lubridate, readr, stringr, tidyr, rlang (>= 1.1.7), tidyselect

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.3.3

Config/pak/sysreqs libicu-dev libxml2-dev libssl-dev libx11-dev
Repository <https://timriffe.r-universe.dev>
Date/Publication 2026-05-07 10:08:35 UTC
RemoteUrl <https://github.com/timriffe/hmdhfdplus>
RemoteRef HEAD
RemoteSha 5cd1cf14a2d795bc217f76ac27ded77b3da392a4

Contents

age2int	2
getCHMDprovinces	3
getHFCcountries	4
getHFDcountries	4
getHFDdate	5
getHFDitemavail	5
getHMDcountries	6
getHMDitemavail	6
getJMDprefectures	7
HFCparse	7
HFDparse	8
HMDparse	9
readCHMDweb	10
readHFD	11
readHFDweb	12
readHMD	13
readHMDweb	14
readJMDweb	15
userInput	17
Index	18

age2int	<i>age2int() convert the Age column from standard HMD or HFD tables to integer</i>
---------	--

Description

Long the bane of many an HMD/HFD user is that the age column must be read into R as a factor or character vector, yet we'd like to use it as integer or numeric. This function strips symbols that are used to indicate the open age groups ("12-", "55+", "110+"), and coerces to integer format. This function is called by HFDparse() and HMDparse(), and so forth.

Usage

age2int(Age)

Arguments

Age a vector of the Age column from and HMD or HFD data object that has been read directly into R. This may be a factor or character vector.

Details

This function is written for the sake of various parse functions.

Value

the same age vector as a clean integer.

Note

original function submitted by Josh Goldstein, modified by Tim Riffe.

Examples

```
AgeTest <- c("12-", "13", "14", "55+")
(AgeNew <- age2int(AgeTest))
AgeNew + .5 # sort of mid-interval

# also handles abrdiged ages properly:
AgeAbridged <- c("0", "1-4", "5-9", "10-14")
age2int(AgeAbridged)
```

getCHMDprovinces	<i>get a named vector of CHMD province codes</i>
------------------	--

Description

This is a helper function to get a vector of 3-character province codes.

Usage

```
getCHMDprovinces()
```

Value

a character vector of 3 character province codes.

Examples

```
## Not run: (provs <- getCHMDprovinces())
```

getHFCcountries	<i>getHFCcountries a function to grab all present country codes used in the Human Fertility Collection</i>
-----------------	--

Description

The function returns a list of population codes used in the Human Fertility Collection (HFC). Optionally, it also can return a data.frame with both the full population name and short code.

Usage

```
getHFCcountries(names = FALSE)
```

Arguments

names	logical. Default FALSE Should a data.frame matching full country names to short codes be given?
-------	---

Value

either a character vector of short codes (default) or a data.frame of country names and codes.

Examples

```
## Not run:
getHFCcountries()
getHFCcountries(names = TRUE)

## End(Not run)
```

getHFDcountries	<i>internal function for grabbing the HFD country short codes.</i>
-----------------	--

Description

This function is called by readHFDweb() and is separated here for modularity. We include both main and provisional countries in the grab.

Usage

```
getHFDcountries()
```

Value

a 'tibble' with three columns 'Country', 'link' and 'CNTRY' (the country short code)

getHFDdate	<i>internal function for grabbing the date of last update for a given HFD country</i>
------------	---

Description

called by readHFDweb(). This assumes that CNTRY is actually available in the HFD.

Usage

```
getHFDdate(CNTRY)
```

Arguments

CNTRY	HFD country short code.
-------	-------------------------

Value

character string of eight integers representing the date as "yyyymmdd".

getHFDitemavail	<i>List the available data item names for a given HFD country.</i>
-----------------	--

Description

called by readHFDweb(). This assumes that CNTRY is actually available in the HFD.

Usage

```
getHFDitemavail(CNTRY)
```

Arguments

CNTRY	HFD country short code.
-------	-------------------------

Value

a tibble of all available data files for the selected country. There are several useful identifiers that can help determine the appropriate file, including the 'measure' and 'subtype' as detected from the html table properties, and 'lexis' and 'parity' as detected either from the file names or the table properties.

getHMDcountries	<i>internal function for grabbing the HMD country short codes.</i>
-----------------	--

Description

This function is called by readHMDweb() and is separated here for modularity. Assumes you have an internet connection.

Usage

```
getHMDcountries()
```

Value

a vector of HMD country short codes.

getHMDitemavail	<i>internal function for grabbing the available data item names for a given country.</i>
-----------------	--

Description

called by readHMDweb() to find file urls. This assumes that CNTRY is actually available in the HFD.

Usage

```
getHMDitemavail(CNTRY)
```

Arguments

CNTRY	character. HMD country short code.
-------	------------------------------------

Value

a tibble of all available data items for the selected country. There are several useful identifiers that can help determine the appropriate file, including the 'measure', 'lexis', 'sex' and interval information, as detected from the item names.

getJMDprefectures	<i>get a named vector of JMD prefecture codes</i>
-------------------	---

Description

This is a helper function for those familiar with prefecture names but not with prefecture codes (and vice versa). It is also useful for looped downloading of data.

Usage

```
getJMDprefectures()
```

Value

a character vector of 2-digit prefecture codes. Names correspond to the proper names given in the English version of the HMD webpage.

Examples

```
## Not run: (prefectures <- getJMDprefectures())
```

HFCparse	<i>HFCparse internal function for modifying freshly read HCD data in its standard form</i>
----------	--

Description

called by readHFC() and readHFCweb(). We assume there are no factors in the given data.frame and that it has been read in from the raw text files using something like: read.csv(file = filepath, stringsAsFactors = FALSE, na.strings = ".", strip.white = TRUE). This function is visible to users, but is not likely needed directly.

Usage

```
HFCparse(DF)
```

Arguments

DF	a data.frame of HFC data, freshly read in.
----	--

Details

This parse routine is based on the subjective opinions of the author...

Value

DF same data.frame, modified so that columns are of a useful class. If there were open age categories, such as "-" or "+", this information is stored in a new dummy column called OpenInterval. Values of 99 or -99 in the AgeInterval column are replaced with "+" and "-", respectively. Year taken from Year1, and YearInterval is given, rather than Year2. Users wishing for a central time point should bear this in mind. The column Country is renamed CNTRY. Otherwise, columns in this database are kept in the data.frame, in case they may be useful.

HFDparse	<i>internal function for modifying freshly read HFD data in its standard form</i>
----------	---

Description

called by readHFD() and readHFDweb(). We assume there are no factors in the given data.frame and that it has been read in from the raw text files using something like: read.table(file = filepath, header = TRUE, skip = 2, na.strings = ".", as.is = TRUE). This function is visible to users, but is not likely needed directly.

Usage

```
HFDparse(DF, item = NULL)
```

Arguments

DF	a data.frame of HFD data, freshly read in.
item	character string of the data product code, which is the base file name, but excluding the country code and file extension .txt. For instance, "mabRR" or "tfrVHbo". This will be passed in, potentially, by the reader.

Details

This parse routine is based on the subjective opinions of the author...

Value

DF same data.frame, modified so that columns are of a useful class. If there were open age categories, such as "-" or "+", this information is stored in a new dummy column called OpenInterval.

HMDparse	<i>internal function for modifying freshly read HMD data in its standard form</i>
----------	---

Description

called by `readHMD()` and `readHMDweb()`. We assume there are no `#factors` in the given `data.frame` and that it has been read in from the raw text files using `#something` like: `read.table(file = filepath, header = TRUE, skip = 2, na.strings = ".#", as.is = TRUE)`. This function is visible to users, but is not likely needed directly.

called by `readHMD()` and `readHMDweb()`. We assume there are no `factors` in the given `data.frame` and that it has been read in from the raw text files using something like: `read.table(file = filepath, header = TRUE, skip = 2, na.strings = ".", as.is = TRUE)`. This function is visible to users, but is not likely needed directly.

Usage

```
HMDparse(DF, filepath)
```

Arguments

DF	a <code>data.frame</code> of HMD data, freshly read in.
filepath	just to check if these are population counts from the name.

Details

This parse routine is based on the subjective opinions of the author...

This parse routine is based on the subjective opinions of the author...

Value

DF same `data.frame`, modified so that columns are of a useful class. If there were `#open` age categories, such as `"-"` or `"+"`, this information is stored in a new `#dummy` column called `OpenInterval`.

DF same `data.frame`, modified so that columns are of a useful class. If there were open age categories, such as `"-"` or `"+"`, this information is stored in a new dummy column called `OpenInterval`.

readCHMDweb

read data from the Canadian Human Mortality Database into R

Description

CHMD data are formatted exactly as HMD data. This function simply parses the necessary url together given a province code and data item (same nomenclature as HMD). Data is parsed using `HMDparse()`, which converts columns into useful and intuitive classes, for ready-use. See `?HMDparse` for more information on type conversions. No authentication is required for this database. Only a single item/prefecture is downloaded. Loop for more complex calls (See examples). The `provID` is not appended as a column, so be mindful of this if appending several items together into a single `data.frame`. Note that at the time of this writing, the finest Lexis resolution for prefectural lifetables is 5x5 (5-year, 5-year age groups). Raw data are, however, provided in 1x1 format, and deaths are also available in triangles. Note that cohort data are not produced for Canada at this time (but you could produce such data by starting with the `Deaths\Lexis` file...).

Usage

```
readCHMDweb(provID = "can", item = "Deaths_1x1", fixup = TRUE, ...)
```

Arguments

<code>provID</code>	a single <code>provID</code> 3 character string, as returned by <code>getCHMDprovinces()</code> .
<code>item</code>	the statistical product you want, e.g., <code>"mltper_5x5"</code> . Only 1.
<code>fixup</code>	logical. Should columns be made more user-friendly, e.g., forcing Age to be integer?
<code>...</code>	extra arguments ultimately passed to <code>read.table()</code> . Not likely needed.

Details

This database is curated independently from the HMD/HFD family, and so file types and locations may be subject to change. If this happens, please notify the package maintainer.

Value

`data.frame` of the data item is invisibly returned

Examples

```
## Not run:
library(HMDHFDplus)
# grab province codes (including All Canada)
provs <- getCHMDprovinces()
# grab all mltper_5x5
# and stick into long data.frame:
mltper <- do.call(rbind, lapply(provs, function(provID){
  Dat      <- readCHMDweb(provID = provID, item = "mltper_5x5", fixup = TRUE)
```

```

        Dat$provID <- provID
        Dat
    )))

## End(Not run)

```

readHFD	<i>readHFD() reads a standard HFD .txt table as a data.frame</i>
---------	--

Description

This calls `read.table()` with all the necessary defaults to avoid annoying surprises. The Age column is also stripped of "-" and "+" and converted to integer, and a logical indicator column called `OpenInterval` is added to show where these were located. Output is invisibly returned, so you must assign it to take a look. This is to avoid lengthy console printouts.

Usage

```
readHFD(filepath, fixup = TRUE, item = NULL, ...)
```

Arguments

<code>filepath</code>	path or connection to the HFD text file, including .txt suffix.
<code>fixup</code>	logical. Should columns be made more user-friendly, e.g., forcing Age to be integer?
<code>item</code>	character string of the data product code, which is the base file name, but excluding the country code and file extension .txt. For instance, "mabRR" or "tfrVHbo". This will be passed in, potentially, by the reader.
<code>...</code>	other arguments passed to <code>read.table</code> , not likely needed.

Details

No details of note.

Value

data.frame of standard HFD output, except the Age column has been cleaned, and a new open age indicator column has been added.

Note

original function submitted by Josh Goldstein, modified by Tim Riffe.

readHFDweb

*read an HFD data file directly from the web as an R data.frame***Description**

Read HFD data directly from the web. This function is useful for short reproducible examples, or to make code guaranteed to always use the most up to date version of a particular HFD data file. For working with the entire HFD for a comparative study, it may be more efficient to download the full HFD zip files and read in the elements using `readHFD()`. This function returns data formatted in the same way as `readHFD()`, that is, with Age columns (and others) converted to integer, and with open age group identifiers stored in a new logical column called `OpenInterval`. It is faster to specify `CNTRY` and `item` as arguments than to make the function figure out what's available. For repeated calls to this function, you can pass your username and password in as variables without having to include these in your R script by using `userInput()`—see example. The user also has the option of querying particular updates from the HFD revision history. If you wish to specify a particular update, you must know the date that a particular country was updated, in the format "YYYYMMDD". These dates differ between countries, so keep a good record if you wish your work to be reproducible to that extent (as well as lightweight)!

Usage

```
readHFDweb(
  CNTRY = NULL,
  item = NULL,
  username = NULL,
  password = NULL,
  fixup = TRUE,
  Update = NULL
)
```

Arguments

<code>CNTRY</code>	character string of the HFD short code. Only one!
<code>item</code>	character string of the data product code, which is the base file name, but excluding the country code and file extension <code>.txt</code> . For instance, "mabRR" or "tfrVHbo". If you're not sure, then leave it blank and a list will be shown. Only one item!
<code>username</code>	your HFD usernames, which is usually the email address you registered with
<code>password</code>	your HFD password. Don't make this a sensitive password, as things aren't encrypted.
<code>fixup</code>	logical. Should columns be made more user-friendly, e.g., forcing Age to be integer?
<code>Update</code>	character string of 8-digit date code of the format "YYYYMMDD". Defaults to most recent update.

Details

You need to register for HFD to use this function: <https://www.humanfertility.org>. It is advised to pass in your credentials as named vectors rather than directly as character strings, so that they are not saved directly in your code. See examples. One option is to just save them in your Rprofile file.

Value

data.frame of the given HFD data file, modified in some friendly ways.

Examples

```
### # this will ask you to enter your login details in the R console
### DAT <- readHFDweb("JPN","tfrRR")
###
### # -----
### # this is a good way to reuse your login credentials without
### # having to reveal them in your R script.
### # if you want to do this in batch then I'm
### # afraid you'll have to find a clever way to
### # pass in your credentials without an interactive
### # session, such as reading them in from a system file of your own.
### myusername <- userInput()
### mypassword <- userInput()
### DAT <- readHMDweb("USA","mltper_1x1",mypassword,myusername)
###
### #-----
### # this also works, but you'll need to make two selections,
### # plus enter data in the console twice:
### DAT <- readHFDweb()
```

readHMD	readHMD() reads a standard <i>HMD</i> .txt table as a data.frame
---------	--

Description

This calls `read.table()` with all the necessary defaults to avoid annoying surprises. The Age column is also stripped of "+" and converted to integer, and a logical indicator column called `OpenInterval` is added to show where these were located. If the file contains population counts, values are split into two columns for Jan 1 and Dec 31 of the year. Output is invisibly returned, so you must assign it to take a look. This is to avoid lengthy console printouts.

Usage

```
readHMD(filepath, fixup = TRUE, ...)
```

Arguments

filepath	path or connection to the HMD text file, including .txt suffix.
fixup	logical. Should columns be made more user-friendly, e.g., forcing Age to be integer?
...	other arguments passed to read.table, not likely needed.

Details

Population counts in the HMD typically refer to Jan 1st. One exception are years in which a territorial adjustment has been accounted for in estimates. For such years, 'YYYY-' refers to Dec 31 of the year before the adjustment, and 'YYYY+' refers to Jan 1 directly after the adjustment (adjustments are always made Jan 1st). In the data, it will just look like two different estimates for the same year, but in fact it is a definition change or similar. In order to remove headaches from potential territorial adjustments in the data, we simply create two columns, one for January 1st (e.g., "Female1") and another for Dec 31st (e.g., "Female2"). One can recover the adjustment coefficient for each year by taking the ratio $V_x = P1(t+1) / P2(t)$. In most years this will be 1, but in adjustment years there is a difference. This must always be accounted for when calculating rates and exposures. Argument fixup is outsourced to HMDparse().

Value

data.frame of standard HMD output, except the Age column has been cleaned, and a new open age indicator column has been added. If the file is Population.txt or Population5.txt, there will be two columns each for males and females.

Note

function written by Tim Riffe.

readHMDweb

readHMDweb a basic HMD data grabber.

Description

Basic HMD data grabber, based on Carl Boe's original HMD2R(). It can grab one or more HMD statistical products, possibly for multiple countries, using a single login session.

Typical pitfalls are removed: the Age column is coerced to integer, while an AgeInterval column is created. Population counts are placed into two columns for Jan. 1 and Dec. 31 of the same year, so as to remove headaches from population universe adjustments. Argument fixup is outsourced to HMDparse().

Usage

```
readHMDweb(
  CNTRY,
  item,
  username,
  password,
  fixup = TRUE,
  validate_items = TRUE
)
```

Arguments

CNTRY	character vector. HMD country letter codes. If not spelled right, or not specified, an interactive menu is offered (if possible).
item	character vector. HMD item code(s), e.g. "fltpcr_1x1". If missing and interactive, you can select from items available in at least one selected country.
username	character. HMD username (usually your email).
password	character. HMD password.
fixup	logical. If TRUE, pass the downloaded table through HMDparse() for convenience.
validate_items	logical. If TRUE (default), item codes are validated against the union of items available across the selected countries.

Details

This function points to the new HMD website (from June 2022). If login fails, you may need to re-register at: <https://www.mortality.org/Account/UserAgreement>.

Value

If a single item ends up with available data: a data.frame (possibly stacked over multiple countries, with PopName as the first column when more than one country is requested).

If multiple items end up with available data: a named list of such data.frames, one per item.

Output is returned invisibly.

Description

JMD data are formatted exactly as HMD data. This function simply parses the necessary url together given a prefecture code and data item (same nomenclature as HMD). Data is parsed using `HMDparse()`, which converts columns into useful and intuitive classes, for ready-use. See `?HMDparse` for more information on type conversions. No authentication is required for this database. Only a single item/prefecture is downloaded. Loop for more complex calls (See examples). The `prefID` is not appended as a column, so be mindful of this if appending several items together into a single `data.frame`. Note that at the time of this writing, the finest Lexis resolution for prefectural lifetables is 5x5 (5-year, 5-year age groups). Raw data are, however, provided in 1x1 format, and deaths are also available in triangles.

Usage

```
readJMDweb(prefID = "01", item = "Deaths_5x5", fixup = TRUE, ...)
```

Arguments

<code>prefID</code>	a single <code>prefID</code> 2-digit character string, ranging from "00" to "47".
<code>item</code>	the statistical product you want, e.g., "fltpcr_5x5". Only 1.
<code>fixup</code>	logical. Should columns be made more user-friendly, e.g., forcing Age to be integer?
<code>...</code>	extra arguments ultimately passed to <code>read.table()</code> . Not likely needed.

Details

No details of note. This database is independently maintained, so file types/locations are subject to change. If this happens, please notify the package maintainer.

Value

`data.frame` of the data item is invisibly returned

Examples

```
## Not run:
library(HMDHFDplus)
# grab prefecture codes (including All Japan)
prefectures <- getJMDprefectures()
# grab all mltper_5x5
# and stick into long data.frame:
mltper <- do.call(rbind, lapply(prefectures, function(prefID){
  Dat      <- readJMDweb(prefID = prefID, item = "mltper_5x5", fixup = TRUE)
  Dat$PrefID <- prefID
  Dat
}))

## End(Not run)
```

`userInput`*userInput let the user type in a character string*

Description

this is useful for asking the user for a username or password, so that it goes directly to a variable and doesn't get inadvertently saved into an R script. There are no arguments. This will only return a character string. This is low key, don't bother using it for data entry. Just type characters, no need to put it in quotes, pressing enter will cause the function to return. Output will not be printed to the console, but it can be assigned directly. This is useful to have as an auxiliary function in case multiple calls to functions such as `readHMDweb()` are desired.

Usage

```
userInput(silent = FALSE)
```

Arguments

<code>silent</code>	logical should a little prompt be given, telling the user to enter text in the console?
---------------------	---

Value

a character string, as given by the user.

Examples

```
### mypassword <- userInput()
### myusername <- userInput()
### DAT <- readHMDweb("USA","mltper_1x1",mypassword,myusername)
```

Index

age2int, [2](#)

getCHMDprovinces, [3](#)

getHFCcountries, [4](#)

getHFDcountries, [4](#)

getHFDDate, [5](#)

getHFDitemavail, [5](#)

getHMDcountries, [6](#)

getHMDitemavail, [6](#)

getJMDprefectures, [7](#)

HFCparse, [7](#)

HFDparse, [8](#)

HMDparse, [9](#)

readCHMDweb, [10](#)

readHFD, [11](#)

readHFDweb, [12](#)

readHMD, [13](#)

readHMDweb, [14](#)

readJMDweb, [15](#)

userInput, [17](#)